

## **Leads, Cords, Cables & Clips**



**Item Number**  
ABL-36 INCH

### **ABL-36 INCH** **Black Silicone Test Lead** 100 cm long with shielded, stackable, retractable banana plugs

The ABL-36 INCH is a Black High Resistance Silicone Test Lead with 2 each shielded, stackable retractable plugs for use with the PAR-809B Variable Resistance Reference and the PGB-745 Decay Accessory Set.

#### **Packaging**

**Weight:** 1 lbs (0.5 kg)  
**Length:** 8.25 Inches (21 cm)  
**Width:** 7.5 Inches (19 cm)  
**Height:** 3.5 Inches (8.5 cm)



**Item Number**  
ARL-36 INCH

### **ARL-36 INCH** **Red Silicone Test Lead** 100 cm long with shielded, stackable, retractable banana plugs

The ARL-36 INCH is a Red High Resistance Silicone Test Lead with 2 each shielded, stackable retractable plugs for use with the PAR-809B Variable Resistance Reference and the PGB-745 Decay Accessory Set.

#### **Packaging**

**Weight:** 1 lbs (0.5 kg)  
**Length:** 8.25 Inches (21 cm)  
**Width:** 7.5 Inches (19 cm)  
**Height:** 3.5 Inches (8.5 cm)



**Item Number**  
PFP-861 LL

### **PFP-861 LL 72 inch Test Lead** 72 inch test lead for use with PFP-861 Stainless Steel Test Plate

The PFP-861 LL is a 72 inch Green Pomona Lead used for grounding and footwear test purposes.

#### **Packaging**

**Weight:** 1 lbs (0.5 kg)  
**Length:** 8.25 Inches (21 cm)  
**Width:** 7.5 Inches (19 cm)  
**Height:** 3.5 Inches (8.5 cm)

**Continued on  
Next Page**



**Item Number**  
PRF-911 GGL

### **PRF-911 GGL**

#### **Green Silicone Test Lead**

**Green grounding lead for PRF-911 Concentric Ring Fixture**

The PRF-911 GGL is a Green High Resistance Silicone Test Lead with 2 each stackable retractable plugs used to ground the PRF-911 Concentric Ring or for general grounding purposes.

**Packaging**

**Weight:** 1 lbs (0.5 kg)  
**Length:** 8.25 Inches (21 cm)  
**Width:** 7.5 Inches (19 cm)  
**Height:** 3.5 Inches (8.5 cm)



**Item Number**  
PRS-800 L

### **PRS-800 L 10 foot**

#### **Silicone Test Lead**

**10 foot silicone lead for use with PRS-800, PRS-801, PRS-812**

10 foot high resistance silicone insulated test lead. Right angle banana plug on one end and a shielded male banana plug on the other.

Test lead to be used with the PRS-800 Megohmmeter, PRS-801 Resistance System Set or PRS-812 Resistance Meter Set.

**Packaging**

**Weight:** 1 lbs (0.5 kg)  
**Length:** 8.25 Inches (21 cm)  
**Width:** 7.5 Inches (19 cm)  
**Height:** 3.5 Inches (8.5 cm)



**Item Number**  
PRS-800 SSL

### **PRS-801 SSL Shielded Test Lead**

**High Resistance Shielded test lead for use with PRS-801**

This High Resistance Shielded test lead is used to make high end resistance measurements with the PRS-801 Resistance System Set or PRS-812 Resistance Meter Set.

**Packaging**

**Weight:** 1 lbs (0.5 kg)  
**Length:** 8.25 Inches (21 cm)  
**Width:** 7.5 Inches (19 cm)  
**Height:** 3.5 Inches (8.5 cm)

**Continued on**  
**Next Page**



**Item Number**  
PRS-801 TVL

**PRS-801 TVL High  
Resistance Voltage Test Lead**  
High Resistance Voltage Test Lead for use with PRS-801

This High Resistance Voltage test lead is used in conjunction with the PRS-801 SSL High Resistance Shielded test lead to make high end resistance measurements with the PRS-801 Resistance System Set or PRS-812 Resistance Meter Set.

**Packaging**

**Weight:** 1 lbs (0.5 kg)  
**Length:** 8.25 Inches (21 cm)  
**Width:** 7.5 Inches (19 cm)  
**Height:** 3.5 Inches (8.5 cm)



**Item Number**  
PFM-711 AC

**PFM-711 AC Analog Output Cable**  
Analog output cable for use with PFM-711A Field Meter

The analog output cable is used to connect to the PFM-711A Field Meter for use with an X-Y Plotter, analog data recorder or timing device.

**Packaging**

**Weight:** 1 lbs (0.5 kg)  
**Length:** 8.25 Inches (21 cm)  
**Width:** 7.5 Inches (19 cm)  
**Height:** 3.5 Inches (8.5 cm)



**Item Number**  
PRS-801

**PRS-801 CIC Computer Input Cable**  
36 inch computer input cable for PRS-801

The PRS-801 CIC, for use with the PRS-801 Resistance System Set, is a RS-232 Data Transmission Cable to standard I/O COM 9 Pin computer ports that let you download your data to standard computer systems via the instrument's RS-232 Output Port.

**Packaging**

**Weight:** 1 lbs (0.5 kg)  
**Length:** 8.25 Inches (21 cm)  
**Width:** 7.5 Inches (19 cm)  
**Height:** 3.5 Inches (8.5 cm)



**Item Number**  
 PRS-800CS

**PRS-800CS Cable Spacers**  
**36 & 10 inch length Cable Spacers with Insulated ends**

This set consists of one 10 inch and one 36 inch Cable Spacer. These are convenient for measuring Point-to-Point according to ESD STM7.1 and ESD STM4.1 using the PRS-801-W 5 lb Conductive Rubber Electrodes.

**Packaging**

**Weight:** 1 lbs (0.5 kg)  
**Length:** 8.25 Inches (21 cm)  
**Width:** 7.5 Inches (19 cm)  
**Height:** 3.5 Inches (8.5 cm)



**Item Number**  
 PRS-800BC

**PRS-801BC Bulldog Clip**  
**Insulated black bulldog clip for use with PRS-800, PRS-801 and PRS-812**

4mm safety plug-on alligator clip, rated 1000V, CAT II, 32A, is fully insulated in polyamide 6.6 and features marked handling areas and overlapping side panels.

This rugged crocodile clip is heavily sprung for good clamping and its brass hinge assures good current distribution.

The clip has a 4 mm rigid socket to accept standard and safety leads and a jaw opening of approximately 20 mm. The clip weighs 13 g.

**Packaging**

**Weight:** 1 lbs (0.5 kg)  
**Length:** 8.25 Inches (21 cm)  
**Width:** 7.5 Inches (19 cm)  
**Height:** 3.5 Inches (8.5 cm)



**Item Number**  
 PRI-870 IAC

**PSI-870 IAC Insulated Alligator Clip**  
**Alligator clip for PSI-870 Rtg use**

Handy accessory clips useful for grounding to equipment and parts.

**Packaging**

**Weight:** 1 lbs (0.5 kg)  
**Length:** 8.25 Inches (21 cm)  
**Width:** 7.5 Inches (19 cm)  
**Height:** 3.5 Inches (8.5 cm)



**Item Number**  
 PRI-870 MAC

**PSI-870 MAC Alligator Clip**  
**Bare metal alligator clip**

Handy accessory clips useful for grounding to equipment and parts.

**Packaging**

**Weight:** 1 lbs (0.5 kg)  
**Length:** 8.25 Inches (21 cm)  
**Width:** 7.5 Inches (19 cm)  
**Height:** 3.5 Inches (8.5 cm)