

COPPER GROUNDING TAPE



Used extensively to pre place a thin conductive grid underlayment for ESD Conductive or Dissipative Flooring Materials including Euro-Stat, XO-Stat, Azo-Stat and Zero-Stat. Excellent for grounding flooring to AC electrical conduit and building ground system. Engineered with a full length, liner covered adhesive backing designed for optimum bond strength to pre-cleaned substrates.

Number	Description	Width	Length
TP-7520	Copper Grounding Tape	1/4"	108'
TP-7521	Copper Grounding Tape	1/2"	108'
TP-7521-1	Copper Grounding Tape	1-1/2"	108'
TP-7523	Copper Grounding Tape	1"	108'
TP-7524	Copper Grounding Tape	2"	108'
TP-7525	Copper Grounding Tape	3"	108'
TP-7528	Copper Grounding Tape	6"	108'
TP-7534	Copper Grounding Tape	12"	108'



Also Available up to 12" wide.

Physical Properties	
Backing thickness	2Mil conductive copper foil
Adhesive thickness	1.5Mil acrylic
Total thickness	3.5Mil
Liner	Paper (yellow color)
Adhesion to steel	17.5 oz/in
Tensile strength	22 lb/in
Elongation	2%
Insulation	UL approved