

Wall Base Performance Properties

PROPERTY	VINYL	RUBBER
TEST DATA		
ASTM 1861-98	Conforms	Conforms
Flame Propagation (UL 992)	<2.0	<2.0
Smoke Density Test (ASTM E 662)	< 450	< 450
Critical Radiant Flux (ASTM E 648 or NFPA 253)	Class I (>0.45 W/cm ²)	Class I (>0.45 W/cm ²)
CONSTRUCTION		
Composition	High grade resin, thermoplastic binders, fillers, and pigments	High grade resin, thermoplastic binders, fillers, and pigments
Gauge	1/8" **	1/8" **
Lengths	4' lengths or 120' roll	4' lengths or 120' roll
Height	2 1/2", 4", 6" **	2 1/2", 4", 6" **
Style	Cove or Straight Toe	Cove or Straight Toe
INSTALLATION		
Adhesive & Spread Rate	#600 Wall Base Adhesive; Covers approximately 275 linear feet of 4" base per gallon	#600 Wall Base Adhesive; Covers approximately 275 linear feet of 4" base per gallon
Trowel Size	3/32" x 3/32" triangular notch with 3/32" flats. If applying adhesive with cartridge gun, use a 2-hole nozzle for a 2 1/2", 3-hole nozzle for a 4", and a 5-hole nozzle for 6".	3/32" x 3/32" triangular notch with 3/32" flats. If applying adhesive with cartridge gun, use a 2-hole nozzle for a 2 1/2", 3-hole nozzle for a 4", and a 5-hole nozzle for 6".
WARRANTY		
One Year*		

* The use of any other adhesive will void VPI's warranty.

** Also refers to Rubber and Vinyl Cove and Straight Base outside corners.

Wall Base Specifications

GENERAL	EXECUTION
REFERENCES	EXAMINATION
A. ASTM F 1861-98: Wall Base	A. Ensure contact wall surface to 1/2 inch below top of base is clean and free from dirt, paint, oil, grease, wall covering, old adhesives, and other extraneous substances.
WARRANTY	B. Beginning of installation means acceptance of surfaces and conditions.
A. Provide manufacturer's warranty under provisions of Section [01700.] [01740.]	INSTALLATION
B. Warranty: Include one year warranty that products are free from defects in materials and workmanship.	A. Fit top set base joints tight and vertical. Install base on solid backing; adhere tightly to wall surfaces. Miter and form internal and external corners as detailed in manufacturer's installation and maintenance instructions. (www.vpiflooring.com)
PRODUCTS	B. Scribe and fit to door frames and other obstructions.
ACCEPTABLE MANUFACTURERS	PROTECTION
A. VPI, LLC (VPI), PO Box 451, Sheboygan, WI 53082-0451	A. Prohibit traffic on finished floor for 48 hours after installation.
FLOOR COVERING MATERIALS	CLEANING
A. Base: [ASTM F 1861-98] VPI Wall Base; top set coved, [2 1/2"] [4"] [6"] inches high, [1/8"] [0.080] inch thick, color [selected.] [scheduled.] (Rubber available in 1/8 inch gauge only.)	A. Remove excess adhesive from floor, base, and wall surfaces without damage, while adhesive is still wet.
Pricing for wall base is determined by color. Specify color.	B. Clean floor and base surfaces.
MANUFACTURING TOLERANCES	
A. Precision control gauge to assure smooth surface with no high edges.	
ADHESIVES	
A. Wall Base adhesive: VPI No. 600 Acrylic Copolymer Wall Base Adhesive. 0 calculated VOCs.	

Complete product information including: architect's material specifications, installation instructions and maintenance, recommended adhesives, code and regulation compliance, warranty information and more is available at www.vpiflooring.com.

VPI Product samples are available upon request:

Phone: 800-874-4240

Fax: 920-458-1368

E-mail: floor@vpicorp.com

Visit: www.vpiflooring.com