

CONDUCTIVE/ STATIC DISSIPATIVE ANTI-FATIGUE



CONDUCTIVE DIAMOND PLATE ANTI-FATIGUE

- Disperse static electricity from an operator the moment they step on the mat and safely away from sensitive equipment.
- 5/32" thick electrically conductive diamond plate surface with a resilient sponge base.
- 9/16" overall thickness with beveled edges.
- Resistivity: Less than 10s OHMS, test method ESD-S7.1 1994.
- Conductive matting should always be used with a ground cord, and the surface kept clean.

| CONDUCTIVE DIAMOND PLATE ANTI-FATIGUE | | |
|--|-----------|----------------|
| STOCK NO. | SIZES | WEIGHT EA. |
| FM-AFC-24X36-1 or 2 | 24" X 36" | 9.0 lbs. |
| FM-AFC-36X60-1 or 2 | 36" x 60" | 25.0 lbs. |
| Custom Sizes - available in lengths up to 75 lin. ft. | | |
| STOCK NO. | SIZES | WEIGHT/LIN.FT. |
| FM.AFD-36-BK-1 or 2* | 36" | 5.0 lbs. |
| FM.AFD-48-BK-1 or 2* | 48" | 6.7 lbs. |
| Color: Black. *Thicknesses: 1" 9/16", 2 - 1" | | |



CONDUCTIVE SMOOTH TOP ANTI-FATIGUE

- Prevent the accumulation of static electricity by quickly draining it from operators and eliminate the hazards of data loss or the damaging of micro-circuitry equipment.
- 1/8" thick conductive smooth surface with a resilient sponge base.
- 1/2" overall thickness with beveled edges.
- Resistivity: Less than 106 OHMS, test method ESD-S7.1 1994.
- Conductive matting should always be used with a ground cord, and the surface kept clean.

| CONDUCTIVE SMOOTH TOP ANTI-FATIGUE | | |
|--|-----------|----------------|
| STOCK NO. | SIZES | WEIGHT EA. |
| FM-AFS-24X36-1 or 2 | 24" X 36" | 9.0 lbs. |
| FM-AFS-36X60-1 or 2 | 36" x 60" | 23.0 lbs. |
| Custom Sizes - available in lengths up to 75 lin. ft. | | |
| STOCK NO. | SIZES | WEIGHT/LIN.FT. |
| FM.AFS-36-BK-1 or 2* | 36" | 4.5 lbs. |
| FM.AFS-48-BK-1 or 2* | 48" | 6.0 lbs. |
| Color: Black. *Thicknesses: 1 - 1/2", 2 - 7/8 | | |



STATIC DISSIPATIVE CORRUGATED ANTI-FATIGUE

- Drain harmful static electricity from personnel, safeguard sensitive electronic equipment.
- 1/8" thick static dissipative corrugated surface with a resilient sponge base.
- 1/2" overall thickness with beveled edges.
- Resistivity: Less than 10⁶ OHMS, test method ESD-S7.1 1994.
- Static dissipative matting should always be used with a ground cord.

| CONDUCTIVE SMOOTH TOP ANTI-FATIGUE | | |
|--|-----------|----------------|
| STOCK NO. | SIZES | WEIGHT EA. |
| FM-AFC-24X36-1 or 2 | 24" X 36" | 9.0 lbs. |
| FM-AFC-36X60-1 or 2 | 36" x 60" | 23.0 lbs. |
| Custom Sizes - available in lengths up to 75 lin. ft. | | |
| STOCK NO. | SIZES | WEIGHT/LIN.FT. |
| FM.AFC-36-BK-1 or 2* | 36" | 4.5 lbs. |
| Color: Black. *Thicknesses: 1 - 1/2", 2 - 7/8 | | |