

# RhinoStat Grit Mats

## Modular Interlocking Floor System

**Anti-Fatigue**  
**97% Recycled**  
**Tapered Edges**  
**Interlocking**  
**Anti-Slip**  
**Free Draining**

### PRODUCT DESCRIPTION

The new innovative interlocking safety mat system designed to provide resilient safe cushioning underfoot.

RhinoStat incorporates all the advantages of the industrial mats in the Ergonomics and antifatigue fields, with the added value of silicon carbide grit. The RhinoStat Modular Interlocking Floor System is the flooring solution where non-slip surfacing is a must in dangerous and slippery conditions.

Available in both Ergo Grit and Ergo Comfort Styles.



**RhinoStat Ergo**

### SPECIFICATIONS

#### Dimensions:

Nominal size of 500mm x 500mm x 25mm (20" x 20" x 1" high). Ramp dimensions 500mm x 100mm x 25mm high (20" x 4" x 1" at highest point).

#### Material:

Recycled P.V.C. and Rubber with UV protection. Plasticized to a shore hardness of 67-80 shore A.

#### Colours:

Black

#### Tests:

Grit Mats have a safe fall height test on concrete of 600mm (23.5 inches). Telarc registered test reports are available on request.

#### Load Capacity:

The safe working load on the mats laid on a rigid base is 4200 kilograms (9282 lbs) per sq ft.

#### Temperature:

Grit Mats are suitable for use in temperatures ranging from minus 30°C (minus 22°F) to plus 90°C (184°F). Mat size increases 0-30°C (86°F): 1mm (1/32") and from 0-50°C (122°F) degrees: 2mm (1/16"). Ramp increase as for mats.

#### Weight:

Mat weight is 2.5 kilos (5.52 lbs). Weight per box of 10 = 25 kgs (55.25 lbs). Ramps weight is 650 grams (1.44 lbs). Weight per box of 8 = 5.2 kgs. (12 lbs).

#### Packaging:

Grit Mats are packed 10 per box, carton size 605mm x 585mm x 130mm (24" x 23" x 5"). Ramps are packed 8 per box. Carton size is 510mm x 200mm x 65mm (20" x 8" x 2.5").

#### Shipping:

A 20 ft container accommodates 6500 Grit Mats packed in 650 cartons. The total product weight is



**RhinoStat Ergo Comfort**



CEDAR VILLAGE EXECUTIVE OFFICES  
4916 26<sup>TH</sup> Street West, Suite 100  
Bradenton, Florida 34207  
Toll Free: 877-463-1376  
Direct Phone: 941-751-7581  
Fax: 1-941-751-7586  
Technical@gndzero.com