



Ground Zero Electrostatics HUMIDITY INDICATOR CARDS

HUMIDITY INDICATOR CARDS


Humidity Indicator Cards (HIC's) are printed with moisture sensitive spots which respond to various levels of humidity with a visible color change from blue to pink. The humidity inside dry packed barrier bags can be monitored by including an HIC inside. When the bag is opened, the card can be examined for proper dryness inside the bag. This indicates that the barrier bag and desiccant functioned correctly.

4-Spot Humidity Indicator Cards

Designed for dry packaging Surface Mount Devices. Monitors the most critical humidity range for SMD's. Color reference bar assists with accurate readings.
Card Size: 2" x 3"
Indicates: 10, 20, 30, 40%
Packing: 100 cards in an air-tight can.

Standards

Complies with EIA 581, MIL-P-116, and MIL-I-8835.




033 Humidity Indicator Card

This card meets the IPC/JEDEC J-STD-033 standard.
Card Size: 2" x 3" inches
Indicates: 5, 10, 15%
Packing: 125 cards in an air-tight can.

Standards

Complies with IPC/JEDEC JSTD-030.




6-Spot Humidity Indicator Card

Used in a variety of dry packaging applications, this card monitors humidity levels across the widest range.
Card size: 1 9/16" x 4 3/4"
Indicates: 10, 20, 30, 40, 50, 60%
Packing: 200 cards in an air-tight can.

Standards

Complies with EIA 581, MIL-P-116, and MIL-I-8835.




3 Spot Humidity Indicator Cards

Popular for military applications, this card is approved for use by DOD, NATO, and governmental agencies for Method II packaging.
Card Size: 2" x 3"
Indicates: 30, 40, 50%
Packing: 125 cards in an air-tight can.

Standards

Complies with MS 20003-2, and MIL-P-116.



Item Number	DESCRIPTION:
HU-4-100	4 Spot Humidity Indicator Card 100/Can
HU-51015-125	5, 10, 15 Spot Humidity Indicator Card 125/Can
HU-6-200	6 Spot Humidity Indicator Card 200/Can
HU-3-125	3 Spot Humidity Indicator Card 125/Can

Specifications

Materials: Blotting paper impregnated with cobaltous chloride.

Accuracy: Based on ambient temperature of 75°F.

Tolerance: Approx. 2.5% for each 10°F away from 75°F.



4916 26th Street West, Suite 100, Bradenton, Florida 34207

Toll Free 877-GND-ZERO (463-1376), **Direct Phone** 941-751-7581 **Fax** 1-941-751-7586

Email sales@gndzero.com

http://www.gndzero.com